



Specifications Philips LED Downlight LuxSpace Mini Deep  
DN561B VLC-E 9W 1350lm 75D - 840 Cool White | 164mm  
- Aluminium Reflector - Dali Dimmable

[View Product](#)

General Information

|                          |                                  |
|--------------------------|----------------------------------|
| SKU                      | 238722                           |
| EAN                      | 8718699970550                    |
| Brand                    | Philips                          |
| Manufacturer Name        | DN561B LED12S/840 PSD-VLC-E C WH |
| Any Lamp all-in warranty | 5 Years                          |
| Average Lifetime (h)     | 70000                            |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 9                 |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |
| Beam Angle (degree)         | 75                |

|                          |                                |
|--------------------------|--------------------------------|
| Luminous Flux (Lumen)    | 1350                           |
| Luminous Efficacy (lm/W) | 159                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 74                             |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Finish of Reflector      | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| EOC8                   | 97055000          |
| Mounting Method        | Recessed          |
| Cut out (mm)           | 150               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | +10 to +25        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | DN561B            |

## Dimensions

Height (mm)

**Why Any-lamp?**

86

Diameter (mm)

164



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

